

< 3 m³/h

< 3 m³/h

Image				
Brand	Biral	Biral	Biral	Biral
Model	PrimAX 25-3 180 RED	PrimAX 25-4 180 RED	AX 10	PrimAX 25-6 180 RED
Options	15-3 130 / 25-3 130 / 32-3 170 / 32-3 180	15-4 130 / 25-4 130 / 32-4 170 / 32-4 180		15-6 130 / 25-6 130 / 32-6 170 / 32-6 180
Energy Efficiency Index (EEI)	0.15	0.16	0.19	0.17
Flow rate (m³/h)	1.8	1.9	1.75	2.75
Head (m)	2.3	3	3	4
Electricity consumption (kWh/period)	44	58	59	95
Available in countries	CH, DE, NL, AT, IT, GB, all others from CH	CH, DE, NL, AT, IT, GB, all others from CH	CH, DE, NL, AT, IT, GB, all others from CH	CH, DE, NL, AT, IT, GB, all others from CH
Image				
Brand	Grundfos	WILO	WILO	HALM
Model	ALPHA2 25-40	Yonos Pico 25/1-4	Stratos Pico 25/1-4	HEP Plus 15-4.0 E 130
Options	32-40	30/01/2004	30/1-4, 15/1-4	20-4.0 / 25-4.0 / HEP Plus 25-4.0 E 180 / 30-4.0
Energy Efficiency Index (EEI)	0.15	0.2	0.2	0.2
Flow rate (m³/h)	1.9	2.2	2.8	2
Head (m)	3	3.5	3.7	2.8
Electricity consumption (kWh/period)	55	56	60	64
Available in countries	EU-25	EU-25	EU-25	EU-25

Image				
Brand	KSB	WILO	Grundfos	KSB
Model	Calio S 25-40	Yonos-Eco 25/1-5	ALPHA2 25-60	Calio S 25-60
Options	15-40, 30-40	30/1-5 BMS	32-60	15-60, 30-60
Energy Efficiency Index (EEI)	0.2	0.2	0.17	0.2
Flow rate (m ³ /h)	2.2	2.95	2.6	2.8
Head (m)	3.5	5	4.5	5
Electricity consumption (kWh/period)	73	93	100	136
Available in countries	EU-25	EU-25	EU-25	EU-25