

< 3 m³/h

< 3 m³/h

Image				
Brand	Biral	Grundfos	Grundfos	WILO
Model	PrimAX 25-3 RED	ALPHA3 25-40	ALPHA2 25-40	Yonos Pico 25/1-4
Options	15-3, 32-3	15-40, 32-40	15-40, 32-40	30/1-4
Energy Efficiency Index (EEI)	0.15	0.15	0.15	0.2
Flow rate (m ³ /h)	1.8	1.7	1.7	2.2
Head (m)	2.3	3	3	3.5
Electricity consumption (kWh/period)	44	53	53	56
Available in countries	on demand	on demand	on demand	on demand
Image				
Brand	Grundfos	Biral	HALM	Biral
Model	ALPHA 1 25-40	PrimAX 25-4 RED	HEP Optimo 25-4.0	AX 25-3 RED (32-3)
Options	15-40, 32-40	15-4, 32-4	15, 20, 30-4.0	G 1½, 2
Energy Efficiency Index (EEI)	0.2	0.16	0.17	0.19
Flow rate (m ³ /h)	1.7	1.9	2.2	1.75
Head (m)	3	3	3.2	2.3
Electricity consumption (kWh/period)	56	58	58	58
Available in countries	on demand	on demand	on demand	on demand

Image				
Brand	Biral	WILO	Biral	WILO
Model	AX 10	Stratos Pico 25/1-4	AX 25-4 RED (15-4, 32-4)	Yonos Pico plus 25/1-4
Options		30/1-4, 15/1-4	G 1, 1½, 2	30, 15/1-4
Energy Efficiency Index (EEI)	0.19	0.16	0.2	0.18
Flow rate (m³/h)	1.75	2.8	1.5	2.75
Head (m)	3	3.75	2.9	3.3
Electricity consumption (kWh/period)	59	60	68	69
Available in countries	on demand	on demand	on demand	on demand
Image				
Brand	KSB	WILO	Biral	Grundfos
Model	Calio S 25-40	Yonos-Eco 25/1-5	PrimAX 25-6 RED	ALPHA 1 25-60
Options	15-40, 30-40	30/1-5 BMS	15-6, 32-6	15-60, 32-60
Energy Efficiency Index (EEI)	0.2	0.2	0.17	0.2
Flow rate (m³/h)	2.2	2.95	2.75	2.65
Head (m)	3.5	5	4	4.5
Electricity consumption (kWh/period)	73	93	95	100
Available in countries	on demand	on demand	on demand	on demand

Image				
Brand	Grundfos	Grundfos	KSB	
Model	ALPHA3 25-60	ALPHA2 25-60	Calio S 25-60	
Options	15-60, 32-60	15-60, 32-60	15-60, 30-60	
Energy Efficiency Index (EEI)	0.17	0.17	0.2	
Flow rate (m³/h)	2.7	2.7	2.8	
Head (m)	4.5	4.5	5	
Electricity consumption (kWh/period)	102	102	136	
Available in countries	on demand	on demand	on demand	